

Magazine Extension Kits - Info & Instructions

Magazine capacity is measured with 2 3/4 inch shells.

The 7 shot extension will hold 1 round in the chamber and 6 rounds in the extension.

The 8 shot extension will hold 1 round in the chamber and 7 rounds in the extension.

The 9 shot extension will hold 1 round in the chamber and 8 rounds in the extension.

The 10 shot extension will hold 1 round in the chamber and 9 rounds in the extension.

Tube lengths

7 Shot is 6 Inches Long

8 Shot is 8 1/8 Inches Long

9 Shot is 10 1/4 Inches Long

10 Shot is 14 3/4 Inches Long

We suggest you change your spring every two years if you leave your shotgun loaded all the time. If you need to order extra springs or need help installing your extension please call us.

Magazine Extension Installation Instructions

1. You will need eye protection! Parts will be under spring pressure. Make sure the shotgun is unloaded and remove all ammo from around the shotgun. Remove the magazine cap from the end of the magazine tube under barrel by unscrewing it.

2. If your shotgun has the metal spring retainer you will have to gently pry it out with a small flat screwdriver. Caution the spring is under pressure, it will jump out of the tube if you are not careful. If you have the new type spring retainer that is a black plastic tube with a slot in the middle you will need to press it down and rotate it 90 degrees or until the slots line up with the dimples on the tube. Then remove it from end of the tube. Parts will be under spring pressure. Remove the spring and shell follower. If you have this kind of retainer you will have to remove the dimples.

3. The new model Remington shotguns have dimples that hold the spring retainer in. If you have this kind of Remington you will need a 3/16 inch (5mm) drill so you can drill each dimple out from the outside of the tube. We recommend the use of a drill press when drilling the dimples out. Once you have drilled them, take a round file and remove all burrs from the inside of the tube so the shell follower will slide freely.

4. You do not have to use the orange follower that comes with the extension, you can use the original follower if you wish. The orange follower has a no tilt tail feature that insures it does not bind in the tube, it also keeps the spring from binding on itself acting as a spring guide. Install the follower on the end of the supplied spring into the tube on the shotgun and then slide the extension tube over the other end of the spring and feed the spring into both tubes as you lower the extension tube onto the end of the magazine tube. Then, screw the extension to the magazine tube while holding the tube straight with the barrel.

5. After installing the magazine extension you will need to install the sling swivel barrel clamp. Look at the clamp from the end to make sure both sides are lined up the same. When looking at the clamp for the end it should resemble a figure eight with the smaller circle on top and the larger circle on bottom. Adjust the nut on the end of the swivel so the clamp is wide enough to slide over the barrel and magazine extension. The small radius of the clamp goes over the barrel, large radius goes over the extension. Place the clamp two, to two and a half inches from the end. You can put the sling swivel on either side of the shotgun. Then turn the sling swivel to tighten the clamp.